

path.data

`path.data` is fairly simple. It contains a mapping of ID's to asset paths.

The file starts with 4 bytes representing a `timestamp` in unix epoch and 4 bytes representing the total number of paths in the file.

Each path consists of a varying number of bytes. The first 4 bytes of a path are the ID, the next 4 bytes are the length of the path in bytes. Reading bytes equivalent to the length will give you a `GB2312` encoded string representing the path.

Example snippet of a `path.data` export.

```
1,Models\npcs\00\000\000\00.ecm
2,Models\npcs\00\000\00000\00000.ecm
3,Models\npcs\00\000\0000\000.ecm
4,Models\npcs\00\000\00000\00000.ecm
5,Models\npcs\00\000\00000\0000.ecm
6,Models\npcs\00\000\000\000.ecm
7,Models\npcs\00\000\000\000.ecm
```

An example C# class representing the data.

```
public class PathData
{
    public Int32 Timestamp { get; set; }
    public Int32 TotalPaths { get; set; }
    public ES0Path[] ES0Paths { get; set; }
}

public class ES0Path : PathData
{
    public Int32 ID { get; set; }
    public Int32 PathLength {get; set;}
    public String? FilePath { get; set; }
}
```

Revision #4

Created 2024-06-21 00:02:53 UTC by Admin

Updated 2024-09-08 15:00:48 UTC by Admin